

MFC-J265w Supported PC Software Functions

Operating System Sistemas operativos		Supported Functions Funciones Soportadas	Interface Conectividad
Windows® ¹	Windows® 2000 Professional ⁵	Printing, Scanning, PC Fax Send ⁴ , Removable Disk ⁶ Impresión, Escaneado, PC Fax Envío ⁴ , Disco extraíble ⁶	USB, Wireless 802.11b/g
	Windows® XP Home ^{2,5} Windows® XP Professional ^{2,5}		
	Windows® XP Professional x64 Edition ²		
	Windows Vista® ²		
	Windows® 7 ²		
	Windows Server® 2003 (print only via network)	Printing Impresión	
	Windows Server® 2003 x64 Edition (print only via network)		
	Windows Server® 2003 R2 (print only via network)		
	Windows Server® 2003 R2 x64 Edition (print only via network)		
	Windows Server® 2008 (print only via network)		
Windows Server® 2008 R2 (print only via network)			
Mac®	Mac OS X 10.4.11, 10.5.x	Printing, PC Fax Send ⁴ , Scanning, Removable Disk ⁶	USB, Wireless 802.11b/g
	Mac OS X 10.6.x	Impresión, Escaneado, PC Fax Send ⁴ , Disco removable ⁶	

MFC-J265w Minimum System Requirements

Operating System Sistemas operativos	Minimum Processor Requirement Requerimiento mínimo de procesador	Recommended RAM Requerimiento de memoria		Hard Disk Space Espacio requerido en el disco duro	
		Minimum RAM	Recommended RAM	For Drivers	For Applications
Windows® 2000 Professional ⁵	Intel® Pentium II® or equivalent	64MB	256MB	110MB	340MB
Windows® XP Home ^{2,5} Windows® XP Professional ^{2,5}		128MB		110MB	340MB

Windows ^{®1}	Windows [®] XP Professional x64 Edition ^{2,5}	64-bit (Intel [®] 64 or AMD64) supported CPU	256MB	512MB	110MB	340MB		
	Windows Vista ^{® 2}	Intel [®] Pentium [®] 4 or equivalent	512MB	1GB	600MB	530MB		
	Windows [®] 7 ²	(Intel [®] 64 or AMD64) supported CPU	1GB (32bit) 2GB (64bit)	1GB (32bit) 2GB (64bit)	650MB	530MB		
	Windows Server ^{®2} 2003 (print only via network)	Intel [®] Pentium [®] III or equivalent	256MB	512MB	50MB	N/A		
	Windows Server [®] 2003 x64 Edition (print only via network)	64-bit (Intel [®] 64 or AMD64) supported CPU						
	Windows Server ^{®2} 2003 R2 (print only via network)	Intel [®] Pentium [®] III or equivalent						
	Windows Server [®] 2003 R2 x64 Edition (print only via network)	64-bit (Intel [®] 64 or AMD64) supported CPU	512MB	1GB				
	Windows Server [®] 2008 (print only via network)	Intel [®] Pentium [®] 4 or equivalent 64-bit (Intel [®] 64 or AMD64) supported CPU		2GB				
	Windows Server [®] 2008 R2 (print only via network)	64-bit (Intel [®] 64 or AMD64) supported CPU						
Mac [®]	Mac OS [®] X 10.4.11, 10.5.x	PowerPC [®] G4/G5 Intel [®] Core [™] Processor	512MB	1GB			80MB	400MB
	Mac OS [®] X 10.6.x and Higher	Intel [®] Core [™] Processor	1GB	2GB				

Conditions:

1. Microsoft® Internet Explorer® 5.5 or greater.
2. For WIA, 1200x1200 resolution. Brother Scanner Utility enables to enhance up to 19200 x 19200 dpi.
3. Third party USB ports are not supported.
4. PC Fax supports black and white only.
5. PaperPort™ 11SE supports Microsoft® SP4 or higher for Windows® 2000 and SP2 or higher for XP.
6. Removable disk is a function of PhotoCapture Center®

For the latest driver updates, visit <http://solutions.brother.com>. All trademarks, brand and product names are property of their respective companies.

Condiciones:

1. Microsoft® Internet Explorer 5.5 ó superior.
2. Resolución de 1200x1200 bajo WIA (sistema de impresión de Windows). La aplicación "Brother Scanner Utility" le permite obtener una resolución mejorada de hasta 19200 x 19200 dpi.
3. No es compatible con puertos USB de terceros..
4. El PC Fax solo funciona en blanco y negro y no soporta papel de tamaño tabloide.
5. PaperPort™ 11SE es compatible con Microsoft® SP4 ó superior para Windows® 2000 y SP2 ó superior para XP.
6. Disco removible es una función del PhotoCapture Center®

Para obtener controladores actualizados visite <http://solutions.brother.com>. Todas las marcas registradas, marcas comerciales y nombres de producto son propiedad de sus respectivas compañías.